

Appl. No. : 09/694,667
Filed : October 23, 2000

C1
Could

lens and a second lens, said auxiliary frame comprising a third lens and a fourth lens, a first attachment housing extending from said first lens, a second attachment housing extending from the second lens, said first attachment housing and said second attachment housing each comprising at least one of an endpiece, a hinge and at least a portion of a closing block, a third attachment housing extending from the third lens, a fourth attachment housing extending from the fourth lens, said third attachment housing extending rearward to abut a portion of said first attachment housing, said fourth attachment housing extending rearward to abut a portion of said second attachment housing, a first securing member embedded within said first attachment housing and a second securing member embedded within said second attachment housing, said first securing member and said second securing member engaging with at least a portion of said third attachment housing and at least a portion of said fourth attachment housing such that said auxiliary frame is secured in position relative to said primary frame.

30. The eyewear of Claim 29, wherein said first securing member is snap.

31. The eyewear of Claim 29, wherein said first securing member is slide.

32. The eyewear of Claim 29, wherein said first securing member is magnet.

33. The eyewear of Claim 32, wherein said third and fourth attachment housings comprise a ferromagnetic material.

34. The eyewear of Claim 32, wherein said third and fourth attachment housing comprise magnets.

35. The eyewear of Claim 32, wherein said magnet comprises a generally horizontal axis and said magnet is exposed on a front surface of said first attachment housing.

36. The eyewear of Claim 32, wherein said magnet comprises a generally horizontal axis and said magnet is exposed on a rear surface of said first attachment housing.

37. The eyewear of Claim 32, wherein said magnet comprises a generally vertical axis and said magnet is exposed on a top surface of said first attachment housing.

38. The eyewear of Claim 32, wherein said magnet comprises a generally vertical axis and said magnet is exposed on a bottom surface of said first attachment housing.

C7 34b
39. (Amended) The eyewear of Claim 29, wherein said first attachment housing comprises said at least a portion of a closing block.

Appl. No. : 094,667
Filed : October 23, 2000

40. The eyewear of Claim 39, wherein said first attachment housing comprises a recess that receives a flange of said closing block.

41. The eyewear of Claim 39, wherein said first attachment housing is split to form said closing block.

42. The eyewear of Claim 41, wherein said first securing member is a magnet and said magnet extends through both portions of said split attachment housing.

43. The eyewear of Claim 39 further comprising a bridge that spans said first attachment housing and said second attachment housing.

44. The eyewear of Claim 43, wherein said first attachment housing comprises an endpiece.

45. The eyewear of Claim 39, wherein said first attachment housing comprises an endpiece.

46. The eyewear of Claim 45, wherein said first attachment housing comprises at least a portion of a hinge.

C3 Sub D2 47. (Amended) The eyewear of Claim 29, wherein said first attachment housing comprises said endpiece.

48. The eyewear of Claim 44, wherein said first attachment housing comprises at least a portion of a hinge.

C4 Sub D2 49. (Amended) The eyewear of Claim 29, wherein said first attachment housing comprises said hinge.

50. The eyewear of Claim 29, wherein said third attachment housing abuts a rear surface of said first attachment housing when said auxiliary frame is mounted to said primary frame.

51. CANCEL

52. CANCEL

53. CANCEL

54. CANCEL

55. CANCEL

56. CANCEL

57. CANCEL

58. CANCEL

C5 Sub D3 59. (Amended) Eyewear comprising a first lens, a second lens, a bridge connecting said first lens to said second lens, a first uniblock connected to said first lens and a second uniblock

Appl. No. : 094,667
Filed : October 23, 2000

connected to said second lens, a first magnetic member embedded within a portion of said first uniblock and a second magnetic member embedded within a portion of said second uniblock, a first rim wire extending at least part way around a circumference of said first lens and having a first end and a second end, a second rim wire extending at least part way around a circumference of said second lens and having a third end and a fourth end, a first closing block connecting said first end and said second end and being at least partially integrally formed with said first uniblock and a second closing block connecting said third end and said fourth end and being at least partially integrally formed with said second uniblock.

60. The eyewear of Claim 59, wherein said first closing block comprises a portion of said first uniblock and a first flange and said second closing block comprises a portion of said first uniblock and a second flange.

61. The eyewear of Claim 60, wherein said first flange is received within a recess formed in said first uniblock and said second flange is received within a recess formed in said second uniblock.

62. The eyewear of Claim 61, wherein said recesses formed in said first and second uniblocks are formed on a lower surface of each of said first and second uniblocks.

63. The eyewear of Claim 59, wherein said first uniblock is formed in a first upper portion and a first lower portion and said second uniblock is formed in a second upper portion and a second lower portion, said first upper portion being connected to said first end, said first lower portion being connected to said second end, said second upper portion being connected to said third end, said second lower portion being connected to said fourth end.

64. The eyewear of Claim 63, wherein said first upper portion and said first lower portion are separated by a generally horizontally extending plane.

65. The eyewear of Claim 63, wherein said first upper portion and said first lower portion and said second upper portion and said second lower portion are separated by a generally horizontally extending plane.

66. The eyewear of Claim 59, wherein said first magnetic member is exposed through a lower surface of said first uniblock and said second magnetic member is exposed through a lower surface of said second uniblock.

67. The eyewear of Claim 59, wherein said first magnetic member is exposed through an upper surface of said first uniblock and said second magnetic member is exposed through an upper surface of said second uniblock.

68. The eyewear of Claim 59, wherein said first magnetic member is exposed through a front surface of said first uniblock and said second magnetic member is exposed through a front surface of said second uniblock.

69. The eyewear of Claim 59, wherein said first magnetic member is exposed through a rear surface of said first uniblock and said second magnetic member is exposed through a rear surface of said second uniblock.

70. The eyewear of Claim 59 further comprising a first temple hingedly connected to said first uniblock and a second temple hingedly connected to said second uniblock.

71. The eyewear of Claim 70, wherein said first uniblock comprises a first integral hinge portion and said second uniblock comprises a second integral hinge portion, said first temple being connected to said first integral hinge portion and said second temple being connected to said second integral hinge portion.

72. The eyewear of Claim 59 further comprising a primary frame, said first magnetic member and said second magnetic member removably connecting said frame to said primary frame.

73. The eyewear of Claim 72, wherein said first magnetic member is exposed through a front surface of said first uniblock.

74. The eyewear of Claim 72, wherein said first magnetic member is exposed through a bottom surface of said first uniblock.

75. The eyewear of Claim 72, wherein said first magnetic member is exposed through a rear surface of said first uniblock.

76. The eyewear of Claim 72, wherein said first magnetic member is exposed through a top surface of said first uniblock.

77. The eyewear of Claim 59 further comprising an auxiliary frame, said first magnetic member and said second magnetic member removably connecting said frame to said auxiliary frame.

78. The eyewear of Claim 77, wherein said first magnetic member is exposed through a front surface of said first uniblock.

79. The eyewear of Claim 77, wherein said first magnetic member is exposed through a bottom surface of said first uniblock.

80. The eyewear of Claim 77, wherein said first magnetic member is exposed through a rear surface of said first uniblock.

81. The eyewear of Claim 77, wherein said first magnetic member is exposed through a top surface of said first uniblock.

82. The eyewear of Claim 59, wherein said first magnetic member comprises a magnet.

83. Eyewear comprising a first lens comprising a front side and a rear side, a temple extending rearward from a side of said first lens, an attachment housing connected to said first lens and extending to a side of said first lens different from said temple, said attachment housing comprising a mounting surface, at least one second lens comprising a front side and a rear side and designed to be worn in front of said first lens, an arm connected to said second lens and extending to a side of said second lens, said arm extending rearward over said attachment housing to abut at least a portion of said mounting surface of said attachment housing, a first magnet connected to one of said attachment housing and said arm and magnetic material attached to the other of said attachment housing and said arm in such a manner that the magnet and the magnetic material are attracted to each other and help to keep the second lens in place with respect to the first lens.

84. The eyewear of Claim 83, wherein said magnet has an axis that extends generally vertically.

85. The eyewear of Claim 83, wherein said magnetic material is a second magnet.

86. The eyewear of Claim 83 further comprising a bridge extending from a side of said primary lens, said bridge extending from the same side of said primary lens as said attachment housing.

87. The eyewear of Claim 83 further comprising a rim wire extending at least part way around said first lens, a flange being secured rim wire and said attachment housing comprising a recess that accommodates said flange.

88. The eyewear of Claim 87, wherein said recess is formed on a lower surface of said attachment housing.

Appl. No. : 09/094,667
Filed : October 23, 2000

89. The eyewear of Claim 88 further comprising a threaded fastener that extends upward through said flange and into said attachment housing.